ServoFit™ Gearheads


The Precision Decision





"we don't say we're best...our customers do"

www.stober.com



The STOBER offering of ServoFit™ gearheads will enable you to fit all your servo needs. The ServoFit™ Precision Planetary Gearheads (SPG) are for compact, highly dynamic applications. The ServoFit™ Modular System (SMS) was designed for those applications where the compact size of a planetary gearhead is not needed. With these two lines, STOBER Drives offers the world's largest variety of servo gearheads.

The STOBER <u>difference</u> = VALUE for you!

3 Rings

 Customer Service/Technical staff answers phone in 3 rings or less.

3 Days


- Standard <u>3 day</u> delivery (Does not apply to PH and PHKX.) Custom motor plates-10 days maximum.
- Emergency 24 hours, no expedite fee

5 Years (Warranty)

 Full 5 year warranty – all reducer components: gears, covers, material and workmanship, etc. Normal wear items (oil seals, bearings, etc.) are covered for 2 years.

Helical Gears

- Highest torque capacity
- Maximum efficiency
- Maintain low noise level



<u>1</u> conventional planetary gearhead produces the same noise level as <u>16</u> Stober planetary gearheads with HeliCamberTM gearing technology.

Exceptional Performance

- Low Noise
- Cool Running
- High Speed Capacity Helical Gears
- High Torque Capacity Helical Gears
- Low Backlash

Fits Any Servo Motor

 Motor plates for the TriAdapt[™] mounting system will fit a wide selection of NEMA, IEC, or custom servo motors.



Application Options

- Stainless steel hardware
 - -Output shafts
 - -Hollow output
 - -Single or double side bushings
- Coatings
 - -Standard severe duty gray paint
 - -White washdown (FDA approved)
 - -Stainless steel (FDA/USDA approved)

Additional Product Offering

- ComTrac[™] Adjustable Speed Drives
- MGS Speed Reducers
- Food and Beverage Duty Speed Reducers
- Poultry Duty Speed Reducers

ServoFit™.... the precision decision.

P Series - SPG

- Backlash < 3 arc/mins
- Ratios 3:1 to 100:1
- Input RPM up to 6000
- Noise Level as low as 58 dB(A)**
- Output Torque from 301 to 7,080 in.lbs.

PH Series - SPG

- Backlash ≤ 3 arc/mins
- Ratios 5:1 to 400:1
- Input RPM up to 6,000
- Noise Level as low as 58 dB(A)**
- Output Torque from 885 to 35,400 in.lbs.

PKX Series - SPG

- Backlash < 6.5 arc/mins
- Ratios 3:1 to 300:1
- Input RPM up to 6,000
- Noise Level as low as 69 dB(A)**
- Output Torque from 354 to 7,080 in.lbs.

PHKX Series - SPG

- Backlash ≤ 5 arc/mins
- Ratios 5:1 to 1,200:1
- Input RPM up to 6,000
- Noise Level as low as 69 dB(A)**
- Output Torque from 885 to 22,125 in.lbs.

F Series - SMS

Backlash:

Standard < 11 arc/mins Reduced < 7 arc/mins

- Ratios 4:1 to 540:1*
- Input RPM up to 4,500
- Noise Level as low as 53 dB(A)**
- Output Torque from 200 to 9,700 in.lbs.

K Series - SMS

Backlash:

Standard ≤ 12 arc/mins Reduced < 6 arc/mins


- Ratios 4:1 to 381:1*
- Input RPM up to 4,500
- Noise Level as low as 53 dB(A)**
- Output Torque from 190 to 106,000 in.lbs.


PE Series - SPG

- Backlash < 15 arc/mins
- Ratios 5:1 to 100:1
- Input RPM up to 8,000
- Noise Level as low as 60 dB(A)**
- Output Torque from 106 to 1,858 in.lbs.

C Series - SMS


- Backlash ≤ 20 arc/mins
- Ratios 2:1 to 276:1*
- Input RPM up to 4,500
- Noise Level as low as 53 dB(A)**
- Output Torque from 97 to 62,000 in.lbs.

















A World of Solutions from a Local Source

STOBER drive systems are readily available around-the-world or around-thecorner from your local STOBER authorized distributors. You can depend on your STOBER distributor for the answers you need and the results you want.



STOBER Drives, Inc. 1781 Downing Drive, Maysville KY 41056 Phone: 606 759-5090, FAX: 606 759-5045, Toll Free: 800 711-3588 Web: www.stober.com, E-mail: sales@stober.com

MGS™, Stober™, ComTrac™, HeliCamber™, and ServoFit™ are registered trademarks of STOBER Drives, Inc. Form No. 3021, Copyright October 2004, Printed in U.S.A.



INDUSTRIAL | LAGZA MEX (55) 53 63 23 31 MTY (81) 83 54 10 18 DIST. AUTORIZADO QRO (442) 1 95 72 60 ventas@industrialmagza.com

